

Features:

- It can realize the customized design scheme
- High directivity within operational band
- Low loss and High isolation


Typical Applications

- Mobile communication field
- GSM,LTE,5G
- Satellite radar, electronic countermeasures
- Test equipment

Electrical&Mechanical Specifications				
Parameter	Min.	Typ.	Max.	Units
Frequency Range	0.4		26.5	GHz
Nominal Coupling	8.5	10	11.5	dB
Frequency Sensitivity		±0.7	±1.0	dB
Directivity	12	14		dB
Insertion Loss (Excl. Coupling)		2.0	2.5	dB
Insertion Loss (true)		2.3	3.0	dB
VSWR Primary		1.5	1.7	: 1
VSWR Secondary		1.5	1.7	: 1
Power Rating	Average	20		W
	Peak	300 (10%DutyCycle,1usPulseWidth)		W
Impedance	50			Ohms
Weight	NA			ounces
Input / Output Connectors	SMA– Female			
Material	Aluminum			
Finish	Oxidation sandblasting			

Environmental Specifications	
Operational Temperature	-40°C~+85°C
Storage Temperature	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment)
Vibration	25gRMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave,3 axis both directions

Outline Drawing:

All Dimensions in mm (inches)

Outline Tolerances ±0.5(0.02)

Mounting Holes Tolerances ±0.2(0.008)

