

Features:

- It can realize the customized design scheme
- High directivity within operational band
- Low loss and High isolation

Typical Applications

- Mobile communication field
- GSM,LTE,5G
- Satellite radar, electronic countermeasures
- Test equipment



Electrical&Mechanical Specifications					
Parameter	Min.	Typ.	Max.	Units	
Frequency Range	6		40	GHz	
Nominal Coupling	19	20	21	dB	
Frequency Sensitivity		±0.5	±0.7	dB	
Directivity	10	14		dB	
Insertion Loss (Excl. Coupling)			1.0	dB	
Insertion Loss (true)		0.9	1.0	dB	
VSWR Primary		1.4	1.6	: 1	
VSWR Secondary		1.4	1.6	: 1	
Power Rating	Average	30			W
	Peak	300 (10%DutyCycle,1usPulseWidth)			W
Impedance	50			Ohms	
Weight	NA			ounces	
Input / Output Connectors	2.92mm– Female				
Material	Aluminum				
Finish	Oxidation sandblasting				

Environmental Specifications	
Operational Temperature	-40°C~+85°C
Storage Temperature	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment)
Vibration	25gRMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave,3 axis both directions

Outline Drawing:

All Dimensions in mm (inches)

Outline Tolerances ±0.5(0.02)

Mounting Holes Tolerances ±0.2(0.008)

